



SDG 800 Series

854-6

Dual-Band Wi-Fi 6 Mesh Ethernet Gateway with 2.5GE Port

Benefits

- True Multi-Gigabit Wi-Fi 6 Ethernet Gateway Delivering Up to 3.6 Gbit/s Capacity
- High-Performance Dual-Band Mesh Wi-Fi for Coverage Across the Home and Property
- 4x4 Simultaneous Streams with MU-MIMO for Lag Free Gaming and 4K Streaming
- H-Pol Omni Antennas Delivering 360 Coverage
- AI-Driven, Mesh Wi-Fi Delivering Consistent, High-Performance Connectivity to All Users and Devices

Overview

The 854-6 Wi-Fi 6 Service Delivery Gateway (SDG) is a carrier-class, 802.11ax Ethernet residential gateway with Dual-band Mesh, 2.5GbE WAN port. It is built to extend fiber and multi-gigabit performance for buffer-free 4K/8K streaming and gaming, connect 100s of smart home devices and deliver consistent coverage across the home or business. The Adtran 854-6 is part of Adtran's next-generation 800 series Ethernet Gateways and Mesh Satellites that enable a consistent multi-user, multi-gigabit experience across the home and property – enabling a transformational Wi-Fi experience.

Smarter, Consistent Whole Home Wi-Fi

The Adtran 854-6 Dual-Band SDG is a true multi-gigabit Ethernet gateway delivering up to 3.6 Gbit/s aggregate throughput for access and backhaul. Combined with innovative H-Pol Omni antennas, the 854-6 SDG delivers 360° coverage anywhere in the home, office, or outdoor spaces.

Carrier-Class Features

The Adtran 854-6 is designed for service providers that require carrier-class performance, reliability, and firmware flexibility in their broadband access gateways. Native support for IPv6, multicast traffic handling for IPTV, dynamic Quality of Service (QoS), and FCC Speed Test are standard features. Out-of-the-box, the Adtran 854-6 SDG offers outstanding interoperability with industry-leading TR-069 remote management systems. The 854-6 includes a 2.5GE WAN interface delivering multi-gigabit wired and wireless throughput.

Speed to Burn and Room to Grow

The 854-6 boasts a Multi-core ARM® Cortex processor with the power to route IPv4/v6 traffic up to 3.6Gbps bi-directionally, with plenty of processing power left over for value-added applications, giving service providers unlimited feature, pricing, and service delivery options.

Performance Personalified

Getting the best Wi-Fi does not mean placing it in a corner closet or a shelving unit behind a glass picture frame. The Adtran 800 series SDGs offer an innovative space-age design that looks great on the desk or shelf while delivering an exceptional Wi-Fi experience to all users and devices.

Product Specifications

Ethernet Interfaces

- 1 x 2.5GBASE-T Ports with RJ-45 Connectors
- 4 x 10/100/1000BASE-T Ports with RJ-45 Connectors
- 1 x 2.5GE SFP Port
- Ethernet Port Auto-Negotiation or Manual Configuration (Software Dependent)
- MDI/MDI-X Automatic Sensing

Gateway Features

- Multiple WAN Services
 - Point-to-Point Protocol over Ethernet (PPPoE)
 - Dynamic Host Configuration Protocol (DHCP)
- DHCP Server for LAN Devices
- DNS Relay
- Network Address Translation (NAT)/Network Address Port Translation (NAPT)
- Port Forwarding
- Static Routing
- Access Control List (ACL)
- VPN Pass-Thru for Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP), and IP Security Protocol (IPSec)
- Firewall
- Application Layer Gateway (ALG)
- Demilitarized Zone (DMZ)
- Dynamic Domain Name Server (DDNS)
- Network Time Protocol (NTP)
- Universal Plug and Play (UPnP)
- IGMP Proxy
- IPv6
 - Stateless Address Autoconfiguration (SLAAC)
 - DHCPv6
 - PPPoEv6
 - DNSv6

WLAN Interface

- Compliant with IEEE 802.11 b/g/n/ac/ax
- Dynamic Frequency Selection
- Multi-Region Support
- 2.4 GHz and 5.0 GHz
 - Dual-Band Radios
 - 2.4 GHz 4x4
 - 5.0 GHz 4x4
- WPA3 Support
- Bluetooth 5.0
- Push Button WPS

USB Interface

- 1 USB Host Interface
- Compliant to USB 3.0

Dimensions

- 9.8 in x 3.5 in x 7.7 in (249 mm x 90 mm x 195 mm) (H x W x D)
- Weight: 2.6 lbs (1176 gm)

Power Supply

- External AC/DC power adapter
- AC Input: 100~240 VAC @ 50/60Hz

Working Environment

- Temperature: 41° F – 104° F (5° C – 40° C)
- Humidity: 5% – 85% Relative Humidity

LEDs

- Multifunction RGBW
- 2.4GHz
- 5GHz
- WPS
- Ethernet Link/Activity

Safety and EMI

- CE Certificate
- FCC/Industry Canada Certified, UL Listed
- ETL Intertek Listed (UL 62368-1)
- CE/UKCA Mark
- DFS Certified
- ACMA/RCM Compliant
- RoHS 6 of 6

SDG 800 Series

Equipment	Region	Part Number
SDG 854-6	North & Central America	17600026FIS
	United Kingdom	17600026F2S
	European Union	17600026F3S
	Australia/New Zealand	17600026F4S
Supported SFPs / ONTs		Part Number
SDX610 1Gbit/s GPON ONT (used with Adtran OLTs)		1442535F3
SDX630 10Gbit/s XGSPON ONT (used with Adtran OLTs)		1287940F1
1G P2P Ethernet SFP up to 10km (used with Adtran OLT-SFP 1442110G1)		1442110G2
1G P2P Ethernet SFP up to 40km (used with Adtran OLT-SFP 1442140G1)		1442140G2



January Copyright © 2024 Adtran, Inc. All rights reserved. Adtran believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. Adtran and the other trademarks listed at www.adtran.com/trademarks are registered trademarks of Adtran, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

Adtran warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty.

Adtran products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of Adtran items (e.g. commodities, technology, software), please visit www.adtran.com/exportlicense.

